

EVIDEN

BullSequana Agility

BullSequana SA21a

The BullSequana Agility family features a versatile range of 1- and 2-socket BullSequana SA servers, manufactured in France and powered by the latest generations of AMD EPYC™ and Intel® Xeon® Scalable processors. The servers are ideally suited for virtualized workloads and all modern architecture patterns, such as private and hybrid clouds, containerized infrastructures, hyper-converged and scale-out solutions. Various GPU options enable acceleration of AI/ML, video processing and image rendering workloads. BullSequana SA servers are delivered as standalone units or fully integrated in racks, along with networking and storage components to drastically reduce time to value.

Combining dual 4th Gen AMD EPYC™ Series processors with fully memory capacity and 12 NVMe drives in a super dense 1U packaging, the **BullSequana SA21a** delivers the highest level of computing and storage performance. It is the preferred platform for virtualization, private and hybrid clouds, high-performance hyper-converged infrastructures, data processing workloads with extreme IOPs, as well as space constrained data centers or edge facilities.

Features

- Dual AMD EPYC™ 9004 Series processor
- 12-channel RDIMM DDR5, 24 x DIMMs
- Dual ROM technology supported
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x Dedicated management port
- 12 x 2.5" NVMe/SAS/SATA hot-swap bays
- 2 x FHHL PCIe Gen5 expansion slots
- 2 x OCP 3.0 Gen5 mezzanine slots
- Dual 1600W 80 PLUS Titanium redundant power supply



Technical specifications

Dimensions	1U (W438 x H43.5 x D700 mm)
CPU	AMD EPYC™ 9004 Series processors Dual processors, 5nm technology Up to 96-core, 192 threads per processor cTDP up to 300W
Memory	24 x DIMM slots 12-Channel DDR5 memory up to 4800 MT/s RDIMM modules up to 64GB supported 3DS RDIMM modules up to 256GB* supported
LAN	2 x 1Gb/s LAN ports (1 x Intel® I350-AM2) Supported NCSI function 1 x 10/100/1000 management LAN
Video	Integrated in Aspeed AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp,
Storage	12 x 2.5" NVMe/SATA/SAS hot-swappable bays SAS card is required for SAS devices support
Expansion Slots	2 x PCIe Gen5 x16 FHHL slots 2 x PCIe Gen5 x16 OCP 3.0 slots Supported NCSI function 3 x M.2 slots (M-key, PCIe Gen3 x4, NGFF-2280/22110)

*256GB: check for availability with your sales representative

Front I/O	1 x USB 3.2 Gen1
Rear I/O	2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN
Backplane I/O bandwidth	PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s
TPM	1 x TPM header with SPI interface Optional TPM2.0 kit
Power supply	Dual 1600W (240V) 80 PLUS Titanium redundant power supply AC input: 100-240V
System fans	8 x 40x40x56 mm (32,000 rpm)
System management	Aspeed® AST2500 management controller Built-in html5 GUI iKVM RBAC, LDAP integration, RADIUS support SNMP, IPMI and Redfish management protocols SNMP trap, email and Redfish event notifications GSM server/ GSM agent for centralize monitoring of multiple BullSequana SA servers
Operating conditions	Operating temperature: 10°C to 35°C (supported configurations depend on temperatures) Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
OS certified	Windows Server 2022 RHEL 9 VMware vSphere 8
Other OS Compatibility	Windows Server 2019 RHEL 8.6 / 8.7 / 8.8 SLES 15 SP4 / 15 SP5 Ubuntu 20.04.6 / 22.04 / 22.04.1 / 22.04.2 / 22.04.3 LTS (x64) VMware ESXi 7.0 Update 3i Citrix Hypervisor r 8.2 LTSR CU