

# EVIDEN

## BullSequana S series

# Technical specifications

To tackle enterprise IT challenges and enable businesses to take full advantage of Artificial Intelligence (AI), Eviden brings to the market a state of the art generation of x86 servers, BullSequana S, optimized for Artificial Intelligence, business critical computing applications and in-memory environments. BullSequana S reaches the highest level of quality of service, performance, availability and scalability to meet IT departments' existing and emerging demands.



### Adapting to business needs

#### Exceptional scalability

To preserve investments and power the most demanding environments, the BullSequana S supports up to 48TB RAM / up to 64TB NVRAM non volatile memory (NVRAM) and up to 32 GPUs.

#### Modularity and flexibility

The BullSequana S can be build or reconfigure to fit exactly your business needs.

#### Operations and TCO benefits for all landscapes

BullSequana S allows up to 20% cost reduction versus classical environments for large cluster virtualization and up to 30% price/performance gain for small and medium SAP HANA landscapes.

### Accelerating digital transformation

#### Powering Enterprise Artificial Intelligence

In order to utilize the extensive capabilities of AI, businesses require an infrastructure with extreme performance. BullSequana S meets the challenge with its unique combination of the most advanced Intel® Xeon® Scalable processors (CPUs) and Graphics Processing Units (GPUs). This innovative architecture, designed by Eviden' R&D teams, enables to mix GPU, storage and compute modules within a single server for ready availability of all workloads.

#### Boosting data analytics & data lake

BullSequana S pre-integrated platform speeds up data lake environments deployments. Its ability to scale as needs arise and adjust with a vast array of internal disks, enables to finely

tune the platform to the business requirements and simplify the lifecycle of new applications.

#### Accelerating in-memory applications

The key element to go real-time is to have all structured data staged in-memory which requires to encompassing specific features. BullSequana S superior scalability, availability and serviceability make it the ideal scale-up platform for very large enterprise applications and in-memory computing.






#### Optimizing IT modernization through virtualization & cloud

BullSequana S is the most agile, scalable and open platform to grow digital business. With its dynamic reconfiguration capabilities, it combines exceptional performance with unparalleled agility and generates efficiencies at every level. It is the go-to server for the private part of a hybrid cloud.

# A powerful and scalable range

Based on a very flexible architecture, the BullSequana S range consists of 5 complementary models assembling one to sixteen 2-socket modules thanks to two types of interconnect:

- a “glueless” interconnect for 1, 2 or 4 modules, allowing to form a glueless topology up to 8 sockets with up to 3 Ultra Path Interconnect (UPI) links per CPU.
- for larger configurations, an eXternal Node Controller (XNC) technology designed and developed by Eviden assumes the ultra-scalability from 8 sockets up to 32 sockets.

BullSequana S200	BullSequana S400	BullSequana S800	BullSequana S1600	BullSequana S3200
				
2 CPUs, up to 3 TB RAM, up to 2 GPUs	up to 4 CPUs, up to 6 TB RAM, up to 4 GPUs	up to 8 CPUs, up to 12 TB RAM, up to 8 GPUs	up to 16 CPUs, up to 24 TB RAM, up to 16 GPUs	up to 32 CPUs, up to 48 TB RAM, up to 32 GPUs

Thanks to a very modular design, each model can be smoothly upgraded to another one, preserving investments and applicative environments. Glue-less configurations can scale-up to 32 sockets by adding UBoxes.

The Compute Box is the base element of the BullSequana S server, with 3 different form factors (2U/4U/8U) hosting one 2-socket module per 2U. A Connecting Box assembles modules within a single Compute Box, on the rear side, with no apparent cabling.

## Key innovative and use-case oriented components

The module is the building block of BullSequana S servers and can be easily extracted from the Compute Box for easy maintenance. The module comprises a Compute unit plus a Storage unit or a GPU unit in option to customize the system to match application requirements.

### Each Compute unit imbeds:

- Two 2nd Generation Intel® Xeon® Scalable processors, with a large choice of models for the best fit with your applications in terms of frequency, number of cores or power consumption
- Up to 24 memory DIMMs, ie a total of up to 3TB per compute module when using 128GB DIMMs
- NVRAM capabilities with the support of Intel® Optane™ DC Persistent Memory (DCPMM) providing near-DRAM performance at a lower-cost. Furthermore, Optane DCPMM can reduce considerably downtime with a much quicker reload of the data when the system restarts.
- Up to 8 disks and hot-plug PCIe blades.

### GPU unit, for artificial intelligence

This option will be used mainly to introduce up to 32 GPUs in a single server in a very flexible way, 2 GPUs per module. Real-time algorithms and machine learning will use this huge processing power to run.

### Storage unit, for data-extensive needs

This unit can hold up to: 12 SAS/SSD 2”5 disks; 4 NL-SAS high capacity 3”5 disks; 4 NVRAM for high I/O throughput. Thanks to this additional Storage unit, the capacity goes up to 20 disks in a 2U form-factor, and more than 2 raw PB in a 32-CPU server. This will be used in various use-cases from data lake to virtualization.

# UNC and UBox for ultra-scalability up to 32 CPUs

The UBox is a 5U chassis imbedding several UPI Node Controllers (UNC). The UNC is the 6th generation of eXternal Node Controller (XNC) designed and developed by Eviden for Intel processor-based servers. It is a VLSI-type (Very Large-Scale Integration) integrated circuit derived from mainframe technologies and tuned for High Performance Computing. This innovative and unique Eviden technology makes it possible to interconnect up to sixteen 2-socket modules allowing to go up to 32-socket SMP systems in a Cache Coherent Non-Uniform Memory Access (CC-NUMA) architecture.

To meet customer application requirements, 2 types of UBox models can be proposed:

- **Enterprise:** this is the standard configuration providing all-to-all topology between CPUs. It provides both the performance and the high availability needed for high memory demanding applications like SAP HANA.
- **High Performance:** well suited for High Performance Computing, doubling the bandwidth in the all-to-all topology between CPUs. It provides exceptional performance for intensive CPU workload.

The UBox is autonomous in term of power, cooling and local management.



## UBox technical specifications

	UBox Enterprise	UBox High-performance
Design		
<b>Form Factor</b>	5U	5U
Processors		
<b>Node Controller Module*</b>	2 <sup>(1)</sup>	4 <sup>(2)</sup>
<b>Node Controller (UNC)</b>	8 <sup>(1)</sup>	16 <sup>(2)</sup>
<b>Power Supply Unit (PSU)</b>	2 for datacenter with 220/240V 3 (N+1 redundancy) or 4 (2N redundancy) for datacenter under 220V/240V	3 (N+1 redundancy) or 4 (2N redundancy) for datacenter with 220/240V
<b>Local Management board</b>	1	1
Cooling		
<b>Fans</b>	12 hot-plug, N+1 redundancy <sup>(1)</sup>	24 hot-plug, N+1 redundant <sup>(2)</sup>
Physical specifications		
<b>Dimensions (HxLxW)</b>	220 (5U) x 446 mm x 850 mm	
<b>Weight</b>	Up to 99 kg	
<b>Operating constraints</b>	Ambient air temperature: +10°C to +35°C, gradient 20°C/hour Relative humidity (non condensing): 20% to 60%, gradient 5%/hour	

\* Node controller module includes UNC's, Power Supplies, Fans, ...

(1) for 8-socket configurations, UBox Enterprise includes 1 Node Controller module with 4 UNC's and 6 fans

(2) for +8-socket configurations UBox High Performance includes 2 Node Controller modules with 8 UNC's and 12 fans

# S200 to S800 technical specifications

	S200	S400	S800
Design			
<b>Form factor</b>	2U	4U	8U
Processors			
<b>Name</b>	Intel® Xeon® Scalable Processors		
<b>Numbers</b>	2 max 56 cores / 112 threads	2 - 4 max 112 cores / 224 threads	2, 4, 6 and 8 max 224 cores / 448 threads
<b>Type</b>	8200, 6200, 5200, 4200 series	8200, 6200, 5200 series	8200 series
<b>Processor cores available</b>	4, 8, 10, 12, 16, 18, 20, 22, 24, 26 or 28	4, 8, 10, 12, 16, 18, 20, 22, 24, 26 or 28	4, 24, 26 or 28
<b>L3 shared cache</b>	77MB	154MB	308MB
Architecture			
<b>Chipset</b>	Intel® C627 Chipset		
<b>Ultra-Path Interconnect (UPI)</b>	Intel® UPI: 2-3 links per socket – up to 10.4 GT/s		
<b>Scalability</b>	2 processors	2 and 4 processors	2, 4, 6 and 8 processors
<b>Hardware partitioning</b>	No	Yes	Yes
Memory			
<b>Memory slots</b>	24	48	96
<b>Min / max DRAM</b>	64 GB – up to 3 TB	128 GB – up to 6 TB	256 GB – up to 12 TB
<b>DRAM type</b>	DDR4 RDIMM, LR-DIMM		
<b>Persistent memory (DCPMM)*</b>	up to 6 TB (12 x 512 GB)	up to 12 TB (24 x 512 GB)	up to 24TB (48 x 512 GB)
Embedded I/O ports			
<b>Network Interface Controller (NIC)</b>	<ul style="list-style-type: none"> <li>4 x 10Gb/s Base-T Ethernet ports or</li> <li>2 x 10Gb/s Optical Ethernet ports (DAC or SFP+) + 2 x 1Gb/s Base-T Ethernet ports</li> </ul>	<ul style="list-style-type: none"> <li>8 x 10Gb/s Base-T Ethernet ports or</li> <li>24x 10Gb/s Optical Ethernet ports (DAC or SFP+) + 2 x 1Gb/s Base-T Ethernet ports</li> </ul>	<ul style="list-style-type: none"> <li>16 x 10Gb/s Base-T Ethernet ports or</li> <li>8x 10Gb/s Optical Ethernet ports (DAC or SFP+) + 2 x 1Gb/s Base-T Ethernet ports</li> </ul>
<b>Management ports</b>	Management interface shared with 1GbE port (plus 100 Mb/s with Private Ethernet management switch for 4S & 8S)		
<b>USB ports</b>	4 x USB 3.0 (3 x front + 1 x internal) + 1 x USB 2.0	4 x USB 3.0 (3 x front + 1 x internal) + 1 x USB 2.0	4 x USB 3.0 (3 x front + 1 x internal) + 1 x USB 2.0
I/O			
<b>I/O slots</b>	Up to 5 Gen3 PCIe x 8 hot pluggable slots (or 2 x 16 + 1 x 8) per Compute Unit		
<b>NIC PCIe blade</b>	1GbE, 10GbE, 25GbE, 100GbE/IB (1,2 or 4 ports per PCI blade according to model)		
<b>HBA PCIe blade</b>	8Gb/s: 2ports per PCIe blade - 16Gb/s: 2 or 4 ports per PCIe blade - 32Gb/s: 2 ports per PCIe blade		
<b>SAS/SATA PCIe blade</b>	12Gb/s: 2 ext. ports per PCIe blade		
Storage			
<b>Compute unit</b>	Hot-pluggable Front Disk Blades		
	Up to 8 x 2.5" SSD/HDDs.	Up to 16 x 2.5" SSD/HDDs.	Up to 32 x 2.5" SSD/HDDs.
<b>Storage unit**</b>	Up to 12 x 2.5" SSDs/HDDs or Up to 4 x 3.5" HDDs or Up to 4 x 2.5" NVMe U.2 drives	Up to 24 x 2.5" SSDs/HDDs or Up to 8 x 3.5" HDDs or Up to 8 x 2.5" NVMe U.2 drives	Up to 48 x 2.5" SSDs/HDDs or Up to 16 x 3.5" HDDs or Up to 16 x 2.5" NVMe U.2 drives
<b>Storage controller</b>	RAID controllers: <ul style="list-style-type: none"> <li>on board SATA 6Gb/s RAID1 controller, up to 2 disks (Compute Unit)</li> <li>SAS 12Gb/s and SATA 6Gb/s, up to 8 disks (Compute Unit) and 12 disks (Storage Unit)</li> </ul> Host Bus Adapter: <ul style="list-style-type: none"> <li>SAS 12Gb/s and SATA 6Gb/s, up to 8 disks (Compute Unit) and 12 disks (Storage Unit)</li> </ul>		
<b>Micro SD</b>	Dual MicroSD (RAID) on internal USB port (VMware boot only for some processors)		
<b>SAN</b>	Dell EMC, HitachiVantara, NetApp, ...		

\* Persistent Memory (DCPMM) is only available for Platinum & Gold processors

\*\* A 2-socket module hosts one Compute Unit and optionally either one Storage Unit or one GPU unit.

	S200	S400	S800
Video			
<b>Video controller</b>	1		
<b>Memory</b>	8 MB		
<b>GPUs: GPU Unit*</b>	Up to 2 GPUs	Up to 4 GPUs	Up to 8 GPUs
Security			
<b>Security features</b>	TPM 2.0 (check for availability), Secure boot, 2-level password		
Power supply			
<b>Hot-swap Power Supply Unit (PSU)</b>	1 + 1 per module		
<b>PSU number</b>	2, redundant	Up to 4, redundant	Up to 8, redundant
<b>PSU type</b>	Label 80+ Titanium & Platinum, 96% efficiency		
<b>Max power output per PSU</b>	2000 watts		
<b>Auto-sensing</b>	220V 60/50Hz		
Cooling			
<b>Fan specifications</b>	Up to 14 hot-plug, N+1 redundant	Up to 28 hot-plug, N+1 redundant	Up to 56 hot-plug, N+1 redundant
Physical specifications			
<b>Dimensions (HxLxW) (max)</b>	89 (2U) x 446 mm (19") x 850 mm	175 (4U) x 446 mm (19") x 850 mm	352 (8U) x 446 mm (19") x 850 mm
<b>Weight</b>	Up to 43 kg	Up to 81 kg	Up to 160 kg
<b>Operating constraints</b>	Ambient air temperature: +10°C to +35°C, gradient 20°C/hour Relative humidity (non condensing): 20% to 60%, gradient 5%/hour		
OS & software			
<b>Operating system</b>	VMware® vSphere (ESXi™), Red Hat® Enterprise Linux®, Suse® Linux Enterprise Server, Microsoft® Windows Server, Oracle VM®, Oracle Linux®		
System management			
<b>BMC</b>	IPMI 2.0		
<b>Remote management</b>	Standard via on-board iBMC (connection through the management port)		
<b>Management software</b>	BMC (Server Hardware Console), IPMI 2.0, RedFish, iCare		
Availability & RAS features			
<b>RAS features</b>	Advanced Error Detection and Correction (AEDC), Viral Mode of error containment, PCIe "Stop and Scream", Virtual (soft) Partitioning, PCI Express ECRC, PCIe Corrupt Data Containment (Data Poisoning), PCIe Link CRC Error Check and Retry, PCIe Link Retraining and Recovery, PCI Express Live Error Recovery, DDR4 Wr Data CRC check/retry, DDR4 Command/Address Parity Check and Retry, Intel® UPI Link Level Retry, Intel® UPI Protocol Protection via 16 bit Rolling CRC, Intel® UPI Dynamic Link width reduction, Core disable for Fault Resilient Boot, Power up, Post Package Repair, Failed DIMM Isolation, PCIe Card Hot Plug (Add/Remove/Swap), PIROM for System Information Storage		
<b>Serviceability</b>	Hot-plug devices: PCIe blades (depending on OS), disks, fans hot-swap devices: Power Supply Unit		
<b>Redundancy</b>	Power supplies, fans, disks with RAID		
Warranty & services			
<b>Standard warranty</b>	3 Years CRU		
<b>Warranty extension</b>	Global Care		
<b>Other services</b>	IT infrastructure Advisory and energy audits Service Assurance HA, capacity and performance management Installation and integration services		
Regulator & safety			
<b>Conformity</b>	Safety (CE, IEC, UL, CSA + APAC certifications), Electromagnetic Compatibility (EC, FCC, ICES-03, VCCI certifications), Environment (RoHS II & WEEE directives, REACH regulation)		

# S1600 technical specifications

## S1600

### Design

<b>Form Factor</b>	21U
--------------------	-----

### Processors

<b>Name</b>	Intel® Xeon® Scalable Processors
<b>Numbers</b>	8 - 10 - 12 - 14 -16 max 448 cores / 896 threads
<b>Type</b>	8200, 6200 series -
<b>Processor cores available</b>	4, 8, 12, 16, 18, 20, 22, 24, 26, 28
<b>L3 shared cache</b>	up to 616 MB

### Architecture

<b>Chipset</b>	Intel® C627 Chipset
<b>Ultra-Path Interconnect</b>	Intel® UPI between sockets and UNC: up to 11.2 GT/s SCI protocol between UNCs: up to 10.4 GT/s
<b>Scalability</b>	8 to 16 processors
<b>Hardware partitioning</b>	Yes

### Memory

<b>Memory slots</b>	up to 192
<b>Min / max DRAM</b>	512 GB - up to 24 TB
<b>DRAM type</b>	DDR4 RDIMM, LR-DIMM ( 64 & 128 GB only)
<b>Persistent Memory (DCPMM)</b>	up to 48 TB ( 96 x 512 GB)

### Embedded I/O ports

<b>Network Interface Controller (NIC)</b>	<ul style="list-style-type: none"> <li>32 x 10Gb/s Base-T Ethernet ports</li> <li>or</li> <li>16 x 10 Gb/s optical Ethernet ports (DAC or SFP+) + 16 x 1Gb/s Base-T Ethernet ports</li> </ul>
<b>Management ports</b>	Management interface shared with 1GbE port (plus 100 Mb/s with Private Ethernet management switch for 16S whatever the configuration).
<b>USB ports</b>	4 x USB 3.0 (3 x front + 1 internal) + 1 x Micro USB 2.0

### I/O

<b>I/O slots</b>	up to 40 Gen3 PCIe x 8 hot pluggable slots (or 16 x16 + 8 x8)
<b>NIC PCIe blade</b>	1GbE, 10GbE, 25GbE, 100GbE/IB (1,2 or 4 ports per PCI blade according to model)
<b>HBA PCIe blade</b>	8Gb/s: 2ports per PCIe blade - 16Gb/s: 2 or 4 ports per PCIe blade - 32Gb/s: 2 ports per PCIe blade
<b>SAS/SATA PCIe blade</b>	12Gb/s: 2 ext. ports per PCIe blade

### Storage

<b>Compute unit</b>	Hot-pluggable Front Disk Blades up to 64 x 2.5" SSD/HDDs
<b>Storage unit**</b>	up to 48 x 2.5" SSD/HDDs or up to 16 x 3.5" HDDs or up to 16 x 2.5" NVMe U.2 drives
<b>Storage controller</b>	RAID controllers: <ul style="list-style-type: none"> <li>on board SATA 6Gb/s RAID1 controller, up to 2 disks (Compute Unit)</li> <li>SAS 12Gb/s and SATA 6Gb/s, up to 8 disks (Compute Unit) and 12 disks (Storage Unit)</li> </ul> Host Bus Adapter: <ul style="list-style-type: none"> <li>SAS 12Gb/s and SATA 6Gb/s, up to 8 disks (Compute Unit) and 12 disks (Storage Unit)</li> </ul>
<b>Micro SD</b>	Dual MicroSD (RAID) on internal USB port (VMware boot only for only some processors)
<b>SAN</b>	Dell EMC, HitachiVantara, NetApp, ...

\*\* A 2-socket module hosts one Compute Unit and optionally either one Storage Unit or one GPU unit.

## S1600

### Video

<b>Video controller</b>	1
<b>Memory</b>	8 MB
<b>GPU unit**</b>	up to 16 NVIDIA GPU cards

### Security

<b>Security features</b>	TPM 2.0 (check for availability), Secure boot, 2-level password
--------------------------	---

### Power supply

<b>Hot-swap Power Supply Unit (PSU)</b>	1 + 1 per module (2 redundant PSU per module)
<b>PSU number</b>	up to 16, redundant
<b>PSU type</b>	Label 80+ Titanium & Platinum, 96% efficiency
<b>Max power output per PSU</b>	2000 watts
<b>Auto-sensing</b>	220V 60/50Hz

### Cooling

<b>Fan specifications</b>	up to 112 hot-plug, N+1 redundant
---------------------------	-----------------------------------

### Physical specifications

<b>Dimensions (HxLxW)</b>	930 (21U) x 446 mm x 850 mm
<b>Weight</b>	up to 415 kg
<b>Operating constraints</b>	Ambient air temperature: +10°C to +35°C, gradient 20°C/hour Relative humidity (non condensing): 20% to 60%, gradient 5%/hour

### OS & software

<b>Operating System</b>	Red Hat® Enterprise Linux®, Suse® Linux Enterprise Server, Oracle Linux®, VMware vSphere (ESXi™) on-going
-------------------------	---

### System management

<b>Baseboard Management Controller (BMC)</b>	IPMI 2.0
<b>Remote management</b>	Standard via on-board iBMC (connection through the management port)
<b>Management software</b>	BMC (Server Hardware Console), IPMI 2.0, RedFish, iCare

### Availability & RAS features

<b>RAS features</b>	Advanced Error Detection and Correction (AEDC), Viral Mode of error containment, PCIe “Stop and Scream”, Virtual (soft) Partitioning, PCI Express ECRC, PCIe Corrupt Data Containment (Data Poisoning), PCIe Link CRC Error Check and Retry, PCIe Link Retraining and Recovery, PCI Express Live Error Recovery, DDR4 Wr Data CRC check/retry, DDR4 Command/Address Parity Check and Retry, Intel® UPI Link Level Retry, Intel® UPI Protocol Protection via 16 bit Rolling CRC, Intel® UPI Dynamic Link width reduction, Core disable for Fault Resilient Boot, Power up, Post Package Repair, Failed DIMM Isolation, PCIe Card Hot Plug (Add/Remove/Swap), PIROM for System Information Storage
<b>Serviceability</b>	Hot-plug devices: PCIe blades (depending on OS), disks, fans hot-swap devices: Power Supply Unit
<b>Redundancy</b>	Power supplies, fans, disks with RAID

### Warranty & services

<b>Standard warranty</b>	3 Years CRU
<b>Warranty extension</b>	Global Care
<b>Other services</b>	IT infrastructure Advisory and energy audits Service Assurance HA, capacity and performance management Installation and integration services

### Regulator & safety

<b>Conformity</b>	Safety (CE, IEC, UL, CSA + APAC certifications), Electromagnetic Compatibility (EC, FCC, ICES-03, VCCI certifications), Environment (RoHS II & WEEE directives, REACH regulation)
-------------------	---

### Connect with us



**eviden.com**

Eviden is a registered trademark © Copyright 2024, Eviden SAS – All rights reserved.